


AO Series Housings

Aluminium
Ports, 1/8" to 1/4"
Element, 12.32.□ to 25.178.□



A0110.209



A0210.201

The AO series filter housings are constructed from anodised aluminium with a stainless steel tie rod and are supplied with a range of connections. The housings are suitable for gas and liquid end of line applications.

Standard housings have NPT ports, but other port types are also available.

Principal Specifications

Housing Model	A0110.209	A0110.209	A0120.209	A0120.201	A0210.209	A0210.201	A0230.209	A0230.201
Port Size - NPT or Other	Ø1/4"	Ø1/8"	Ø1/4"	1/8"	Ø1/4"	1/4"	Ø1/4"	1/4"
Maximum Temperature - °C	150	150	150	150	150	150	150	150
Materials of Construction (1)								
Head & Bowl	AL	AL	AL	AL	AL	AL	AL	AL
Tie Rod	SS	SS	SS	SS	SS	SS	SS	SS
Principal Dimensions								
A - mm	15	15	15	15	25	25	25	25
B - mm	19	19	19	19	36	36	36	36
C - mm	58	58	83	83	93	93	207	207
Weight - grams	40	40	60	60	120	125	130	135
Filter Element Code (2)	12.32.□	12.32.□	12.57.□	12.57.□	25.64.□	25.64.□	25.178.□	25.178.□

Notes (1) Material abbreviations - AL = Aluminium, SS = Stainless Steel

(2) Replace the □ with the grade required, e.g. 25.64.5K, 25.64.S25V, 25.64.T20