Materials 316L Stainless Steel


Pressure 500 psi Ports 3/4" to 2" Element 51.476.□

SS434 series filter housings are specified for 3/4" and 1" line size applications up to 500 psi. For applications over 500 psi higher pressure versions are available, see the SS435, SS436, and SS438 filter housings.

Standard housings have NPT ports and a Viton seal. Other seal types are available as an option. BSPT and BSPP port types are also available.

The housings are free from welds and comply with NACE MR-01-75 and are CE marked in accordance with PED 97/23/EC.

These housings can also be supplied in a wide range of exotic materials, such as Hastelloy, Monel, Titanium etc.





Technical Specifications

Housing Model	SS434.521	SS434.621	SS434.721	SS434.821
Port Size	3/4" NPT	1" NPT	1&1/2" NPT	2" NPT
Drain	1/4" NPT	1/4" NPT	1/4" NPT	1/4" NPT
Maximum Pressure, psi (1)	500	500	500	500
Maximum Temperature, °F (2)	390	390	390	390
Materials of Construction (3)				
Head, Bowl & Internals	316L SS	316L SS	316L SS	316L SS
Seal (4)	Viton	Viton	Viton	Viton
Filter Element Code (5)	51.476.□	51.476.□	51.476.□	51.476.□
Adsorber Cartridge Code (6)	51.476.AD□	51.476.AD□	51.476.AD□	51.476.AD□
Principle Dimensions in inches				
Diameter	4.35	4.35	5.50	5.50
Height	25.10	25.10	25.80	25.80
Volume, cc	2450	2450	2510	2510
Weight, lbs	19.60	19.60	24.85	24.85
Accessories				
Support Core	SCSS43	SCSS43	SCSS43	SCSS43
Mounting Bracket	MBSS42	MBSS42	MBSS42	MBSS42

Notes

- (1) Above 390°F the pressure rating is reduced, consult us for the exact rating at any specific temperature
- $(2) Maximum temperature 390 ^{o} Fusing standard seal. For temperatures up to 615 ^{o} Fuse a Chemraz seal (2) Maximum temperature 390 ^{o} Fusing standard seal. For temperature sup to 615 ^{o} Fuse a Chemraz seal (2) Maximum temperature (3) ^{o} Fuse a Chemraz seal (3) ^{o}$
- (3) Material abbreviations, 316L SS = 316L Stainless Steel
- $(4) Add \, suffix \, for \, other \, seal \, types, \, PTFE = .T, Chemraz = .C, \, Nitrile = N, \, Kalrez = .K, \, EPDM = .E, \, Silicone = .S, \, (e.g. \, SS434.521.T)$
- (5) Replace the \square with the grade required, e.g. 51.476.5CK, 51.476.S20V, 51.476.T20
- (6) Replace the \square with the type required, e.g. 51.476.AD01



Contact Us

Classic Filters Ltd.
Sextant Park
Neptune Close
Rochester
Kent
England
ME2 4LU

T +44 (0)1634 724224
F +44 (0)1634 724234
E info@classicfilters.com
W www.classicfilters.com

Follow Us



http://www.linkedin.com/company/classic-filters-ltd.



http://www.twitter.com/classicfilters