Materials 316L Stainless Steel


Pressure 350 Bar Ports 1/8" or 1/4" Element 12.32.□

SV117 series filter housings are specified for 1/8" & 1/4" line size coalescing applications. The housing is designed so the ports and drain connection are all arranged in the head. This means that the drain does not have to be disconnected to change the filter element and the element remains vertical which is the correct orientation for efficient coalescing.

Standard housings have NPT ports and include Viton seals. Other seal types are available as an option. BSPT and BSPP port types are also available.

The housings are free from welds and comply with NACE MR-01-75 and are CE marked in accordance with PED 97/23/EC.

These housings can also be supplied in a wide range of exotic materials, such as Hastelloy, Monel, Titanium etc.





## **Technical Specifications**

Port Size       1/8" NPT       1/4" NPT         Drain       1/8" NPT       1/4" NPT         Maximum Pressure, Bar (1)       350       350         Maximum Temperature, °C (2)       200       200         Materials of Construction (3)         Head, Bowl & Internals       316L SS       316L SS	Housing Model	SV117.111	SV117.221
Drain         1/8" NPT         1/4" NPT           Maximum Pressure, Bar (1)         350         350           Maximum Temperature, °C (2)         200         200           Materials of Construction (3)         350         350			
Maximum Pressure, Bar (1)       350       350         Maximum Temperature, °C (2)       200       200         Materials of Construction (3)       350       200	Port Size	1/8" NPT	1/4" NPT
Maximum Temperature, °C (2) 200 200  Materials of Construction (3)	Drain	1/8" NPT	1/4" NPT
Materials of Construction (3)	Maximum Pressure, Bar (1)	350	350
	Maximum Temperature, °C (2)	200	200
Head, Bowl & Internals316L SS316L SS	Materials of Construction (3)		
	Head, Bowl & Internals	316L SS	316L SS
Seals (4) Viton Viton	Seals (4)	Viton	Viton
Filter Element Code (5) 12.32.□ 12.32.□	Filter Element Code (5)	12.32.□	12.32.□
Principal Dimensions in mm	Principal Dimensions in mm		
Diameter 44 44	Diameter	44	44
Height 80.5 80.5	Height	80.5	80.5
Volume, cc 25 25	Volume, cc	25	25
Weight, kg 0.55 0.55	Weight, kg	0.55	0.55
Accessories	Accessories		
Mounting Bracket MBSV117 MBSV117	Mounting Bracket	MBSV117	MBSV117

## Notes

- $(1) Above 200 {^\circ}\!C \ the \ pressure \ rating \ is \ reduced, consult \ us \ for \ the \ exact \ rating \ at \ any \ specific \ temperature$
- (2) Maximum temperature 200 °C using standard seal. For temperatures up to 324 °C use a Chemraz seal
- (3) Material abbreviations, 316L SS = 316L Stainless Steel
- (4) Add suffix for other seal types, Chemraz = .C, Nitrile = N, Kalrez = .K, EPDM = .E, Silicone = .S, (e.g. SV117.221.E)
- (5) Replace the  $\square$  with the grade required, e.g. 12.32.5CK



## **Contact Us**

Classic Filters Ltd.
Sextant Park
Neptune Close
Rochester
Kent
England
ME2 4LU

T +44 (0)1634 724224

F +44 (0)1634 724234

E info@classicfilters.com

W www.classicfilters.com

## **Follow Us**



http://www.linkedin.com/company/classic-filters-ltd.



http://www.twitter.com/classicfilters