Materials 316L Stainless Steel

Pressure 350 Bar

Ports 1/8", 1/4" & 1/2"

Element 12.32. □


Magnet 13/18.25.MAG

SS127.MG series filter housings are based on our standard SS127 series and have both a filter element & Neodymium magent in one housing.

Special and custom housing can also be supplied with internal arrangements to suit spcific aplications.

Standard housings have NPT ports and a Viton seal. Other seal types are available as an option. BSPT and BSPP port types are also available.

The housings are free from welds and comply with NACE MR-01-75 and are CE marked in accordance with PED 97/23/EC.





Technical Specifications

| Housing Model | SS127.101.MG | SS127.111.MG | SS127.201.MG | SS127.221.MG | SS127.401.MG | SS127.421.MG |
|-------------------------------|-----------------------|-----------------------|--------------|-----------------------|-----------------------|-----------------------|
| Port Size | 1/8" NPT | 1/8" NPT | 1/4" NPT | 1/4" NPT | 1/2" NPT | 1/2" NPT |
| Drain | None | 1/8" NPT | None | 1/4" NPT | None | 1/4" NPT |
| Maximum Pressure, Bar (1) | 350 | 350 | 350 | 350 | 350 | 350 |
| Maximum Temperature, °C (2) | 200 | 200 | 200 | 200 | 200 | 200 |
| Materials of Construction (3) | | | | | | |
| Head, Bowl & Internals | 316L SS | 316L SS | 316L SS | 316L SS | 316L SS | 316L SS |
| Seal (4) | Viton | Viton | Viton | Viton | Viton | Viton |
| Filter Element Code (5) | 12.32.□ | 12.32.□ | 12.32.□ | 12.32.□ | 12.32.□ | 12.32.□ |
| Magnet Code | 13/18.25 . MAG | 13/18.25 . MAG | 13/18.25.MAG | 13/18.25 . MAG | 13/18.25 . MAG | 13/18.25 . MAG |
| Principal Dimensions in mm | | | | | | |
| Diameter | 36 | 36 | 36 | 36 | 50 | 50 |
| Height | 103.5 | 103.5 | 103.5 | 103.5 | 115.5 | 115.5 |
| Volume, cc | 35 | 35 | 35 | 35 | 37.5 | 37.5 |
| Weight, kg | 0.5 | 0.5 | 0.5 | 0.5 | 0.87 | 0.87 |
| Accessories | | | | | | |
| Support Core | SCSS11 | SCSS11 | SCSS11 | SCSS11 | SCSS11 | SCSS11 |
| Mounting Bracket | MBSS11 | MBSS11 | MBSS11 | MBSS11 | MBSS11 | MBSS11 |

Notes

- (1) Above 200°C the pressure rating is reduced, consult us for the exact rating at any specific temperature
- (2) Maximum temperature 200°C using standard seal. For temperatures up to 324°C use a Chemraz seal
- (3) Material abbreviations, 316L SS = 316L Stainless Steel
- $(4) Add \ suffix for \ other \ seal \ types, PTFE=.T, Chemraz=.C, Nitrile=N, Kalrez=.K, EPDM=.E, Silicone=.S, (e.g. SS125.221.T.MG)$
- (5) Replace the \square with the grade required, e.g. 12.32.SS100, 12.32.S20V,



Contact Us

Classic Filters Ltd.
Sextant Park
Neptune Close
Rochester
Kent
England
ME2 4LU

T +44 (0)1634 724224

F +44 (0)1634 724234

E info@classicfilters.com

W www.classicfilters.com

Follow Us



http://www.linkedin.com/company/classic-filters-ltd.



http://www.twitter.com/classicfilters