Materials 316L Stainless Steel

Pressure 100 or 350 Bar

Ports 1/4" to 1"


**Element** 12.32. □ to 51.230. □

The SF series housings are designed for fast loop and bypass applications. The internal volume is kept to a minimum for a fast response time. The straight-through flow design gives a flushes the filter elements to increase the service life.

Standard housings have NPT ports and a Viton seal. Other seal types are available as an option. BSPT and BSPP port types are also available.

The housings are free from welds and comply with NACE MR-01-75 and are CE marked in accordance with PED 97/23/EC where required.

These housings can also be supplied in a wide range of exotic materials, such as Hastelloy, Monel, Titanium etc.





## **Technical Specifications**

| -                             |           |           |           |           |           |
|-------------------------------|-----------|-----------|-----------|-----------|-----------|
| Housing Model                 | SF117.221 | SF127.221 | SF215.421 | SF235.421 | SF425.421 |
| Port Size                     | 1/4" NPT  | 1/4" NPT  | 1/2" NPT  | 1/2" NPT  | 1" NPT    |
| Sample Outlet                 | 1/4" NPT  |
| Bar (1)                       | 350       | 350       | 100       | 100       | 100       |
| Maximum Temperature, °C (2)   | 200       | 200       | 200       | 200       | 200       |
| Materials of Construction (3) |           |           |           |           |           |
| Head, Bowl & Internals        | 316L SS   |
| Seal (4)                      | Viton     | Viton     | Viton     | Viton     | Viton     |
| Filter Element Code (5)       | 12.32.□   | 12.57.□   | 25.64.□   | 25.178.□  | 51.230.□  |
| Principal Dimensions in mm    |           |           |           |           |           |
| Diameter                      | 50        | 50        | 63        | 63        | 100       |
| Height                        | 71        | 96        | 115       | 232       | 331       |
| Volume, cc                    | 15        | 26        | 95        | 245       | 840       |
| Weight, kg                    | 0.8       | 1.0       | 1.6       | 3.3       | 10.0      |
|                               |           |           |           |           |           |

## Notes

- (1) Above 200°C the pressure rating is reduced, consult us for the exact rating at any specific temperature
- (2) Maximum temperature 200°C using standard seal. For temperature up to 324°C use a Chemraz seal
- (3) Material abbreviations, 316L SS = 316L Stainless Steel
- $(4) Add \ suffix for \ other \ seal \ types, PTFE=.T, Chemraz=.C, Nitrile=N, Kalrez=.K, EPDM=.E, Silicone=.S, (e.g. \ SL215.421.T)$
- (5) Replace the  $\Box$  with the grade required, e.g. 12.32.5K, 12.32.S20V



## **Contact Us**

Classic Filters Ltd.
Sextant Park
Neptune Close
Rochester
Kent
England
ME2 4LU

T +44 (0)1634 724224

F +44 (0)1634 724234

E info@classicfilters.com

W www.classicfilters.com

## **Follow Us**



http://www.linkedin.com/company/classic-filters-ltd.



http://www.twitter.com/classicfilters