
Materials 316L Stainless Steel

Pressure 6000 psi

The SS218 and SS238 Adsorber Housings are a simple but high performance solution for the adsorption of various chemical vapours in a gaseous stream. The hollow tube, with integral filter diverts the gas flow to the base of the bowl allowing complete passage of gas through the adsorber granules. Simply remove the filter bowl without disturbing the line connections to replace the used adsorber media. It is recommended to use a coalescing filter housing as a pre-filter to remove liquid aerosols and droplets.

Housings are available with 1/4" or 1/2" ports and have NPT ports and Viton seals. Other seal types are available as an option. BSPT and BSPP port types are also available.

A range of granular adsorber materials are available and these are listed below. together with the principle uses. We are pleased to advise about any special applications you may have. The media is supplied in resealable plastic containers and two sizes are available, 1 litre or 4 litres.





## **Technical Specifications**

Housing Model	SS218.201.AD	SS218.201.AD	SS238.201.AD	SS238.401.AD
Port Size	1/4" NPT	1/2" NPT	1/4" NPT	1/4" NPT
Drain	None	None	None	None
Maximum Pressure, psi	6000	6000	6000	6000
Maximum Temperature, °F	390	390	390	390
Materials of Construction				
Head, Bowl & Internals	316L SS	316L SS	316L SS	316L SS
Seal	Viton	Viton	Viton	Viton
Filter Pads	PE	PE	PE	PE
Principal Dimensions in inches				
Diameter	3.35	3.35	3.35	3.35
Height	5.80	5.80	10.40	10.40
Volume, cc	160	160	160	160
Weight, lbs	5.60	5.60	8.25	8.25
Accessories	5.00	2.00	20	
Mounting Bracket	MBSS218	MBSS218	MBSS218	MBSS218

G	irade	Adsorber	Principle Uses
0.	1	Activated Carbon Granules	Removal of hydrocarbons and other organic vapours
03	3	Molecular Seive 4A	Removal of CO2, NH3, H2S, SOx
04	4	Molecular Seive 13X	Removal of CO2, NH3, H2S, SOx, aromatics, amines
0.5	5	Silica Gel (Blue)	Removal of water vapour
0.5	5a	Silica Gel (Orange)	Removal of water vapour
06	6	Mixed Bases (SodaLime)	Removal of acidic gases, CO2, SOX, NOX, HCI
07	7	Potassium Permanganate	Removal of SOX and other acidic gases
08	8	Hopcalite	Removal of CO by catalytic oxidation to CO2



## **Contact Us**

Classic Filters Ltd.
Sextant Park
Neptune Close
Rochester
Kent
England
ME2 4LU

T +44 (0)1634 724224

F +44 (0)1634 724234

E info@classicfilters.com

W www.classicfilters.com

## Follow Us



http://www.linkedin.com/company/classic-filters-ltd.



http://www.twitter.com/classicfilters