Disposable Filter Elements Dimensions & Tolerances

Disposable Filter Element Dimensions & Tolerances

Filter elements are available in a wide range of standard diameters and lengths. These are based on traditional industry standard sizes and allow the element to be installed in other proprietary equipment.

This chart shows you a list of all our standard disposable filter elements, particulate and coalescing, along with their actual sizes in millimetres and the standard tolerances we use in manufacturing.

Particulate Types									
Element Code	Inside Ø	Tolerance	Outside Ø	Tolerance	Length	Tolerance			
10.32.□	10.0	±0.25	14.0	±0.50	32.0	±0.25			
10.57.□	10.0	±0.25	14.0	±0.50	57.0	±0.25			
12.20.□	12.5	±0.25	17.0	±0.50	20.0	±0.25			
12.25.□	12.5	±0.25	17.0	±0.50	25.4	±0.25			
12.32.□	12.5	±0.25	17.0	±0.50	32.0	±0.25			
12.57.□	12.5	±0.25	17.0	±0.50	57.0	±0.25			
16.32.□	16.0	±0.25	22.0	±0.50	32.0	±0.25			
16.41.□	16.0	±0.25	22.0	±0.50	41.0	±0.25			
25.30.□	25.5	±0.25	31.0	±0.50	30.0	±0.25			
25.51.□	25.5	±0.25	31.0	±0.50	51.0	±0.25			
25.64.□	25.5	±0.25	31.0	±0.50	64.0	±0.25			
25.127. 🗆	25.5	±0.25	31.0	±0.50	127.0	±0.25			
25.178.□	25.5	±0.25	31.0	±0.50	178.0	±0.25			
38.58.□	38.5	±0.25	45.0	±0.50	58.0	±0.25			
38.89.□	38.5	±0.25	45.0	±0.50	89.0	±0.25			
38.115.□	38.5	±0.25	45.0	±0.50	115.0	±0.25			
38.152.□	38.5	±0.25	45.0	±0.50	152.0	±0.25			
38.178.□	38.5	±0.25	45.0	±0.50	178.0	±0.25			
51.89.□	51.5	±0.25	59.0	±0.50	89.0	±0.25			
51.230.□	51.5	±0.25	59.0	±0.50	230.0	±0.25			
51.476.□	51.5	±0.25	59.0	±0.50	476.0	±0.25			
63.476.□	63.5	±0.25	72.0	±0.50	476.0	±0.25			
63.762.□	63.5	±0.25	72.0	±0.50	762.0	±0.25			

Coalescing Types									
Element Code	Inside Ø	Tolerance	Outside Ø	Tolerance	Length	Tolerance			
10.57.□	10.0	±0.25	18.0	±0.50	32.0	±0.25			
10.57.□	10.0	±0.25	18.0	±0.50	57.0	±0.25			
12.32.□	12.5	±0.25	19.0	±0.50	32.0	±0.25			
12.57.□	12.5	±0.25	19.0	±0.50	57.0	±0.25			
25.35.□	25.5	±0.25	35.0	±0.50	35.0	±0.25			
25.64.□	25.5	±0.25	35.0	±0.50	64.0	±0.25			
27.64.□	27.0	±0.25	39.0	±0.50	64.0	±0.25			
25.127. 🗆	25.5	±0.25	35.0	±0.50	127.0	±0.25			
25.178.□	25.5	±0.25	35.0	±0.50	178.0	±0.25			
38.58.□	38.5	±0.25	50.0	±0.50	58.0	±0.25			
38.89.□	38.5	±0.25	50.0	±0.50	89.0	±0.25			
38.115.□	38.5	±0.25	50.0	±0.50	115.0	±0.25			
38.152.□	38.5	±0.25	50.0	±0.50	152.0	±0.25			
38.178.□	38.5	±0.25	50.0	±0.50	178.0	±0.25			
51.89.□	51.5	±0.25	64.0	±0.50	89.0	±0.25			
51.230.□	51.5	±0.25	64.0	±0.50	230.0	±0.25			
51.476.□	51.5	±0.25	64.0	±0.50	476.0	±0.25			
63.476.□	63.5	±0.25	76.0	±0.50	476.0	±0.25			
63.762.□	63.5	±0.25	76.0	±0.50	762.0	±0.25			



Special Sizes

Special size filter elements can also be produced that are not included on this chart. We can manufacture in a wide range of different diameters and lengths.

Please enquire if you have any specific requirements.



Contact Us

Classic Filters Ltd.
Sextant Park
Neptune Close
Rochester
Kent
England
ME2 4LU

T +44 (0)1634 724224

F +44 (0)1634 724234

E info@classicfilters.com

W www.classicfilters.com

Follow Us



http://www.linkedin.com/company/classic-filters-ltd.



http://www.twitter.com/classicfilters