
Materials PTFE & Pyrex Glass


Pressure 100 psi Ports 1/8" or 1/4" Element 12.57.□ Membrane MT.33.□

FGM121 combination housings have a coalescing filter element and a PTFE membrane in a single unit.

The porous PTFE membrane is supported by a sintered porous PTFE disc on the outlet side. The wet sample gas enters the inlet port and then through the coalescing element to remove the bulk of the liquid and solid particles and then to the membrane. Any liquid in the gas sample will flow to the drain port. This port can also be used as a bypass function for the main flow.

Standard housings have NPT ports and include Viton seals. Other seal types are available as an option. BSPT and BSPP port types are also available.





## **Technical Specifications**

Housing Model	FGM121.111	FGM121.221
Port Size	1/8" NPT	1/4" NPT
Drain & Bypass Ports	1/8" NPT	1/4" NPT
Maximum Pressure, psi	100	100
Maximum Temperature, °F (1)	210	210
Materials of Construction (2)		
Head, & Internals	PTFE	PTFE
Bowl	Pyrex	Pyrex
Seals (3)	Viton	Viton
Filter Element Code (4)	12.57.□	12.57.□
Membrane Code (5)	MT.33.□	MT.33.□
Principle Dimensions in inches		
Diameter	1.95	1.95
Height	5.70	5.70
Volume, cc	45	45
Weight, lbs	1.30	1.30
Accessories		
Mounting Bracket	MB.SM115	MB.SM115

## Notes

- (1) Maximum temperature of 210°F is due to the Pyrex bowl
- (2) Material abbreviations, PTFE = Polytetrafluoroethylene
- $(3) Add \ suffix for \ other seal \ types, PTFE=.T, Chemraz=.C, Nitrile=N, Kalrez=.K, EPDM=.E, Silicone=.S, (e.g. FGM.221.T)$
- (4) Replace the  $\Box$  with the element grade required, e.g. 12.57.5CK
- (5) Replace the  $\hfill\Box$  with the membrane grade required, e.g. MT.33.M2



## **Contact Us**

Classic Filters Ltd.
Sextant Park
Neptune Close
Rochester
Kent
England
ME2 4LU

T +44 (0)1634 724224

F +44 (0)1634 724234

E info@classicfilters.com

W www.classicfilters.com

## Follow Us



http://www.linkedin.com/company/classic-filters-ltd.



http://www.twitter.com/classicfilters